


SN# 000149 Lamp Specific Acceptance Test




Model: UV-4700, Profusion XW	Result	Steady State	Acceptable	Units
Lamp Specific Acceptance Test	Pass	369 —	365 ± 5	nm
Full Width Half Maximum (FWHM)	Pass	12 —	≤ 15	nm
Full Width at 10% Maximum	Pass	25 —	≤ 30	nm
Longest Wavelength at Half Maximum	Pass	375 —	≤ 377	nm
Max Excitation Irradiance (347-382 nm)	Pass	8,957 —	≥ 7,000	μW/cm ²



Inspector: REL CORP. IN MHP
 Date of Certification: 10.14.2025

This lamp has been tested to conform to all requirements of:
 ASTM E3022 ✓ AITM6-1001 ✓ ISO 3059 ✓ RRES 90061 ✓

Emission Spectrum Measured at Stabilization Temperature with Blue-wave UV-25 S/N 22011404, Certificate Number 22011404-UV-CR2-1124



Profusion XW Series, Certificate of Conformance



SN# 000149	Switch On	Steady State	Elevated Temp*	Acceptable	Units
Peak Output Wavelength	368	369	370	365 ± 5	nm
Full Width Half Maximum (FWHM)	12	12	13	≤ 15	nm
Full Width at 10% Maximum	25	25	27	≤ 30	nm
Longest Wavelength at Half Maximum	374	375	376	≤ 377	nm
Visible Emission	20	18	15	≤ 20	Lux
Max Excitation Irradiance (347-382 nm)	10,300	8,957	7,100	7,000	μW/cm ²
Irradiance at Peak Output Wavelength	788	685	520	-	μW/cm ²
Body Stabilization Temp (70°F Ambient)	-	92	-	≤ 120	°F
Current Ripple	9	9	9	≤ 35	mA peak-peak

* Tested in a 115°F Environment, the maximum ambient temperature where still light meets all requirements

All testing was conducted at 24 inches from sensor unless otherwise noted

