




SN# 001406 Lamp Specific Acceptance Test

Model: UV-4700, Profusion XW	Result	Steady State	Acceptable	Units
Lamp Specific Acceptance Test	Pass	370 -	365 ± 5	nm
Full Width Half Maximum (FWHM)	Pass	11 -	≤ 15	nm
Full Width at 10% Maximum	Pass	22 -	≤ 30	nm
Longest Wavelength at Half Maximum	Pass	375 -	≤ 377	nm
Max Excitation Irradiance (347-382 nm)	Pass	7,316 -	≥ 7,000	μW/cm ²




Inspector: MUR
Date of Certification: 6-28-2026

This lamp has been tested to conform to all requirements of:

ASTM E3022 ✓ AITM6-1001 ✓ ISO 3059 ✓ RRES 90061 ✓

Emission Spectrum Measured at Stabilization Temperature with Blue-wave UV-25 S/N 18120729, Certificate Number 18120729-UV-CR2-0925



Profusion XW Series, Certificate of Conformance



SN# 001406	Switch On	Steady State	Elevated Temp*	Acceptable	Units
Peak Output Wavelength	369	370	370	365 ± 5	nm
Full Width Half Maximum (FWHM)	11	11	13	≤ 15	nm
Full Width at 10% Maximum	22	22	27	≤ 30	nm
Longest Wavelength at Half Maximum	374	375	376	≤ 377	nm
Visible Emission	20	18	15	≤ 20	Lux
Max Excitation Irradiance (347-382 nm)	8,413	7,316	7,100	7,000	μW/cm ²
Irradiance at Peak Output Wavelength	718	625	520	-	μW/cm ²
Body Stabilization Temp (70°F Ambient)	-	92	-	≤ 120	°F
Current Ripple	9	9	9	≤ 35	mA peak-peak

* Tested in a 115° F Environment, the maximum ambient temperature where light still meets all requirements

All testing was conducted at 24 inches from sensor unless otherwise noted

